Association for Information Systems AIS Electronic Library (AISeL)

ECIS 2012 Proceedings

European Conference on Information Systems (ECIS)

5-2-2012

A COMPARISON AND VALIDATION OF 13 CONTEXT META-MODELS

Christine Bauer Vienna University of Economics and Business

Follow this and additional works at: http://aisel.aisnet.org/ecis2012

Recommended Citation

Bauer, Christine, "A COMPARISON AND VALIDATION OF 13 CONTEXT META-MODELS" (2012). ECIS 2012 Proceedings. 17. http://aisel.aisnet.org/ecis2012/17

This material is brought to you by the European Conference on Information Systems (ECIS) at AIS Electronic Library (AISeL). It has been accepted for inclusion in ECIS 2012 Proceedings by an authorized administrator of AIS Electronic Library (AISeL). For more information, please contact elibrary@aisnet.org.

A COMPARISON AND VALIDATION OF 13 CONTEXT META-MODELS

Bauer, Christine, Vienna University of Economics and Business, Institute for Management Information Systems, Augasse 2-6, UZA II, 1090 Vienna, Austria, chris.bauer@wu.ac.at

Abstract

'Context' is a significant element in the field of context-aware and pervasive computing. Thereby, a context meta-model defines context on an abstract level. Simultaneously, a context meta-model builds the basis for specific context models that support system designers in their decisions which context variables to integrate in a particular intelligent context-adaptive system. This paper compares 13 meta-models with respect to their scope. Taking an empirical approach, we matched the meta-models against context variables used in research practice. On the one hand, the meta-models find themselves well reflected by research practice, in a sense that the models' context categories can be described by context variables reported in research. On the other hand, the results clearly indicate that each of the 13 context meta-models fails to describe the full landscape of context. Many context variables used in reported research are not covered by any of the analysed context meta-models. Accordingly, this paper calls on the research community to advance its basic theories continuously because the research field needs theories that reflect reality.

Keywords: Context meta-models, Model comparison, Pervasive computing, Context, Review.

1 Introduction

Already back in the 1990's researchers started to engage with context-aware computing (Schilit and Theimer, 1994). Since then, the community has grown rapidly. The vision is that technology is intelligently weaved into our everyday lives (Weiser, 1991) and systems adapt their behaviour according to the context they run in (e.g., Ferscha et al., 2002, Brown et al., 1997, Ferscha et al., 2004). In such pervasive computing environments, users frequently interact implicitly or indirectly with an intelligent system without having to be aware that they are using a system in the moment.

One significant element in the pervasive computing field is known as 'context'. The scale of definitions of context shows a broad spectrum. Early attempts to define the context resulted in enumerations of examples (e.g., Schilit and Theimer, 1994, Dey, 1998) or choosing synonyms for context (e.g., Brown et al., 1997). The basis for many definitions was provided by Dey and Abowd (2000), "context is any information that can be used to characterize the situation of an entity". This definition, though, is very broad and generic. Similarly, Soylu et al. (2009) point out that "context is an open concept since it is not limited with one's imagination". In contrast, other definitions are highly specific to a certain application (e.g., Müller and Krüger, 2009, Bauer and Spiekermann, 2011).

Due to the challenge to define context verbally in one sentence, researchers started to elaborate context meta-models using graphical notations. A context meta-model is a generic description of the context world on a meta-level that is not targeted towards a particular system. Furthermore, a context-meta model builds the basis for translating it into context models for specific context-adaptive systems, which finally guide system designers in determining which context variables to consider for a particular context-adaptive system. However, a scale of context meta-models exists and the community could not yet agree on a single one.

Against this background, the present paper provides an overview of existing context meta-models and compares them with respect to their comprehensiveness. Furthermore, we discuss how these context meta-models are reflected in the current research practice in the pervasive computing field.

The paper is structured as follows: First, the reader is introduced to the field of comparing models as well as context meta-models (Section 2, related work). Section 3 essentially describes the applied methods for comparison and validation. Then the paper presents the comparison of 13 context meta-models in detail (Section 4). In Section 5, the paper discusses the findings and interprets them, before the paper concludes with a summary and an outlook to future work (Section 6).

2 Related work

2.1 Approaches to compare models

The most basic characteristic of a model is that it is an abstraction of reality. Accordingly, each model represents reality with a varying level of completeness (Peuquet, 1984).

When comparing two models, the main task is to calculate the mappings and the differences between models (Lin et al., 2004). Comparing models at a high level of abstraction is challenging though (Kolovos et al., 2006). Manual comparison is tedious, time consuming, and prone to error. Accordingly the modelling community seeks for automation of model comparison and visualisation of the results (Lin et al., 2004).

Fundamental issues of model comparison – whether done manually or automatically – is what properties of models need to be compared and at which level to compare them (Lin et al., 2004). Having decided on these issues, Kolovos et al. (2006) suggest to compare models pairwise. First it is necessary to partition model elements into following categories: (1) elements for which matching

elements exist in the opposite model and (2) elements for which matching elements do not exist in the opposite model. For matching elements, it is necessary to further judge the conformance match or mismatch between them (e.g., two elements may match in their names but one is declared as abstract while the other as concrete). For elements that do not have a matching counterpart in the opposite model, we differentiate between elements that are included in the domain of the comparison operation and those that are excluded. However, before being able to compare the elements, once has to set up rules that indicate whether two elements match and/or conform to each other. This issue, though, is specific to the models' domains, frameworks, and particular characteristics and cannot be answered from a general perspective.

2.2 Context meta-models

Although many people believe to understand the notion of 'context', they are rarely able to verbally express its meaning and are also not in a position to distinguish it clearly from non-context (Dey, 2001).

For the scope of this work, context is approached from a requirements engineering point of view (cf. Sitou and Spanfelner, 2007, Bauer and Spiekermann, 2011). We define context as the sum of "measurable and logically disjunctive information units, all of which must be combined to create an adaptive service" (Bauer and Spiekermann, 2011).

While a *context model* specifies relevant context for a particular context-adaptive service or system, a *context meta-model* structures context on a generic meta-level and is not bound to any specific system.

Already in the 1990's, some scholars recognized the need to define and structure context. Since then, a scale of context meta-models has been proposed. Common categories used to understand context include a user's location and environment, the identities of nearby people and objects (entities), and changes to those entities (Dey, 1998, Schilit et al., 1994).

Basically, we differentiate existing context meta-models by their *degree of abstraction* from the real world context. Context meta-models with a high level of abstraction depict the context world with a few generic categories. Context meta-models with a low level of abstraction typically depict the context world on two levels, with rather generic categories on the first level of abstraction and more specific categories on a deeper level. Frequently explicit examples enrich these models (on a third level of abstraction). Table 1 provides an overview of 13 context meta-models with their context categories, grouped by their level of abstraction.

publication	level of abstraction	additional information				
	1st level	2nd level	3rd level			
high level of abstract	ion					
Chen and Kotz	physical environment			build on Schilit et al. (1994)		
(2000)	user environment					
	computing environment					
	time					
Sitou and	operational environment			closely geared to Tara-		
Spanfelner (2007)	participants			sewich (2003); considers		
	activities			change over time		
Han et al. (2008)	user with his or her internal context			considers time by including		
	social context			past, present, and future on		
	physical context			a time line		
Black et al. (2009)	task					
	location					
	objects					
Schilit and Theimer	user's location and environment					
(1994)	the identities of nearby people and					
	objects (entities)					
	changes to entities					
Schilit et al. (1994)	physical environment	e.g., lighting, noise level		where you are, who you are		
	user environment	location	with, and what resources			
		collection of nearby people		are nearby		
		social situation				
	computing environment	available processors				

		devices accessible for user input and		
	1	display		
		network capacity		
		connectivity		
		costs of computing		
Bradley and Dunlon	user's world	incidental		combines and builds upon
(2005)		meaningful		existing models from
(2005)	application's world	incidental		linguistics psychology and
	application's world	mendentai		computer science
		meaningtui		computer science
	contextual world	task		
		physical context		
		social context		
		temporal context		
		cognitive context		
		application's context		
low level of abstracti	on	upplication o content		
Rodden et al. (1008)	infrastructure context	neonle		cotegories are enumerated
Roducii et al. (1998)	anniasti deture context	devices		in an unstructured manner
	application context	devices		in an unstructured manner
	system context	objects		
	location context	presence		
	physical context	identity		
		space		
		time		
	1	position		
Schmidt et al	environment	human factors		
(1999a)		nhysical space	-	
(1)))(1)	colf	physical space	physical state	-1
	seif	user	physiological state	
			cognitive state	
		device	device state	_
	activity	task		
		user behaviour		
Schmidt et al.	human factors	information about users themselves		considers time aspect as
(1999b)		users' social environment		context history over time
(users' tasks		
	physical anyironment	location		
	physical environment	location		
		infrastructure		
		conditions	light	
			pressure	
			acceleration	
			audio	
			temperature	
Tarasewich (2003)	environment	location and orientation of objects	1	considers time with respect
Turuse wieli (2005)	environment	physical properties		to present past and future
		brightness and noise levels		to present, past, and fature
		availability		
		quality		
	participants	location and orientation		
		personal properties		
		mental state		
		physical health		
	1	expectations		
	activities	tasks and goals of participants		
1	activities	avents in the apprironment	e a weather	-1
Zainal and M-1	avtrincia contant	physical anvironment	c.g., weddiei	+
Zamoi and Nakata	extrinsic context	physical environment	-	
Tarasewich (2003) Zainol and Nakata (2010)		social environment	_	
	1	computing entity	_	
		location		
	intrinsic context (user)	user's personal profile		
		preferences		
		emotional state		
	interface context	activity		
		service	-	
Sign at al. (2010)	location	geographical		
51gg et al. (2010)	location	relativo	-	
	time		_	
	ume	period	_	
		relative		
	activity	action		
		task		
	constitution	biological		
		mood	-	
	environment	physical	-	
	en an onnient	tashnalagigal	-	
		technological	-	
		equipment	_	
	identity	user	_	
	1	social		
1	1	organizational		

Table 1.Overview of context meta-models with their levels of abstraction

3 Methods

In this work, we compare the 13 context meta-models as presented in Section 2.2 with respect to their scope (context meta-model comparison). In doing so, we investigate how well existing context meta-models cover the context variables used in this research area. Furthermore, we evaluate how well the context categories of these meta-models are reflected in research practice in the pervasive computing field (context meta-model validation).

The specific research questions are: How similar are the existing context meta-models? How comprehensive are these context meta-models? How well are the context meta-models reflected in pervasive computing research practice?

3.1 Model comparison approach

We iteratively reviewed the context meta-models as described in Section 2.2. Adopting an inductive approach, we first identified the context variables on the top level of abstraction that were named identically in several meta-models and grouped them accordingly. Other context variables had temporarily built separate groups. Reviewing these 'temporary' groups for semantic conformity led to a reduction of groups. The meta-models' context variables on the second level of abstraction were used to ensure that semantic conformity was interpreted as intended by the models' authors. Further brainstorming and group discussions led to a refinement of the grouping structure. In a final step, names were given to the resulting groupings, which we refer to as 'context dimensions'.

3.2 Validation approach

To develop an effective sampling strategy, we made a scoping review of the published literature. We decided to take the sample from IEEE Pervasive Computing Magazine, since this is the main outlet of the scientific and professional community in the field. We included all full-length articles of the IEEE Pervasive Computing Magazine, from 2005 through to the articles available in June 2011 (volume 4, issue 1 – volume 10, issue 2).

The following article categories of the 'IEEE Pervasive Computing Magazine' were included in the sample: Applications, News, Smart Phones, Spotlight, Standards & Emerging Technologies, Wearable Computing, and Works in Progress. Out of the 414 articles in the scope of the reviewed issues, a total of 297 met our inclusion criteria.

The coding procedure had three steps:

In a first step, we extracted basic information from each article: (1) author and year of publication, (2) title of the article, as well as (3) volume and issue. Additionally, two reviewers coded inductively from raw data (the articles) and obtained the following information: (4) explicitly stated context variables (i.e. the word or any deflection form of it is explicitly mentioned in the article) and (5) implicitly stated context variables (i.e. the context variable is circumscribed in the article; e.g., 'rate of the vehicle's speed change' is coded as 'acceleration and deceleration'). A total of 10,498 variables (9,867 explicit, 631 implicit) were coded (including duplicates among different articles, while duplicate occurrences within one article were filtered).

In a second step, we applied a 'word stemming' procedure for the explicitly and implicitly stated context variables. This procedure eliminates redundancy by uniting different terms that have the same base form. For example, 'locations' is coded as 'location'. Applying the word stemming procedure resulted in 3,742 distinct context variables (meta-codes).

In a third step, we took a deductive approach using the context dimensions as outlined in Section 4.1. Two reviewers allocated each coded variable (meta-codes) to a corresponding context dimension, if a

corresponding one existed. All meta-codes that could not be allocated to one of the context dimensions were subsumed under the general term 'others'.

Two reviewers coded each article and jointly built the classification scheme. In nearly every case, agreement on all coded dimensions was obtained. In the few instances, where some disagreement emerged, the reviewers discussed the variable in question until consensus could be established.

4 Results

4.1 A comparison of context meta-models

By iteratively reviewing the context meta-models as described in Section 2.2 we could identify six overarching context categories, which we refer to as context dimensions. Table 2 provides an overview of the six context dimensions and indicates which dimensions the various context-meta models cover.

authors	context dimensions											
	physical world	individual	social groups	activity	technology	change over time						
Schilit et al.	physical	user			computing							
(1994)	environment	environment			environment							
Schilit and	location,	identities of				changes						
Theimer	objects	people										
(1994)												
Rodden et	location,				application,							
al. (1998)	physical				system,							
		10			infrastructure							
Schmidt et	environment	self	• 1	activity	1							
al. (1999a)	physical	physiological	social	behaviour,	device state							
		state,		<i>task</i>								
Sabmidt at	physical	buman factors				change over						
al (1000h)	environment	numan factors				time						
Chen and	physical	user			computing	time						
Kotz (2000)	physical	user			computing	time						
Tarasewich	environment	participants		activities		present, past.						
(2003)		F				future						
Bradley and		user			application							
Dunlop												
(2005)												
Sitou and	operational	participants,		activities		change over						
Spanfelner	environment	internal				time						
(2007)												
Han et al.	physical		social			past, present,						
(2008)	1			. 1		future						
Black et al.	location,			tasks								
(2009)	objects	• • • • • •			inter Court							
Zainol and	extrinsic	intrinsic			interface							
(2010) Sign of al	location	identity		activity								
(2010)	environment	constitution		activity								
	environment	constitution	1	1		1						

Table 2.Overview of context meta-models with their context categories

The 'physical world' refers to everything concerned with the physical environment, the location (e.g., absolute location, relative orientation), and objects as part of the physical environment. While the dimension 'individuals' connotes context that concerns single persons and not groups (e.g., identity, eye colour, physiological states), the dimension 'social groups' refers to groups in their social environment (e.g., community, social pressure). Furthermore, the meta-models seem to use activity and task as closely related terms describing very similar variables. We therefore joined these two concepts as one dimension termed 'activity'. In defining the infrastructure category, most authors actually refer to computing resources, networks or communication infrastructure. Accordingly, we subsumed this category under the dimension 'technology' (e.g., device, computing environment, application). Additionally, we believe that this term seems to better reflect this type of context. Most – but not all – context meta-models consider changes to context variables (over time) as separate context variable. We reflected this by keeping 'change over time' as a separate context dimension (e.g., changes, past-present-future).

Interestingly, although 'identity' is frequently mentioned in enumerative definitions and simple taxonomies of context (Dey and Abowd, 2000, Rodden et al., 1998), it is rarely used explicitly in the context meta-models (e.g., Sigg et al., 2010). Most models consider identity as a facet of the 'individuals' dimension.

4.2 Context-dimension validation: Context dimension richness

As reported in the methods section, data includes a total of 3,742 distinct meta-codes. Figure 1 illustrates the distribution of meta-codes among context dimensions. The more meta-codes a dimension refers to, the 'richer' it is. However, a high number of meta-codes also indicates that the respective dimension is rather complex and potentially too broad to support system designers.



Figure 1. Number of meta-codes describing the context dimensions

The dimension 'physical world' is the richest context dimension. Here we identify that this dimension is rather broadly defined and accordingly subsumes a scale of meta-codes (1,024). Thereof, the variable 'location' alone accounts to 340 different meta-codes. The multi-facetted way of describing the subtleties of location is confirmed by Dobson (2005), who demonstrates a non-exhaustive taxonomy of eighteen distinct ways to locate a person.

The dimension 'individuals' is described by 702 different meta-codes. This strong representation may be due to a strong focus on human-computer interaction in the community. Furthermore, this high number reflects the complexity of human beings. For instance, the 'individuals' dimension includes personality traits, people's behaviour, physiological aspects, and attitudes.

As soon as people interact with other people or organisations, we refer to it as the 'social groups' dimension. 304 meta-codes describe these phenomena, which ranges in the middle.

Similar to the 'individuals' dimension, also the 'technology' dimension is strongly represented (630 meta-codes). This is not surprising because the pervasive computing community is strongly represented by computer scientists who approach the field from a technical perspective and work towards technology advancement. Furthermore, similar to human beings, also the technology and computing field is very complex.

When analysing the dimension 'activity' (138 meta-codes), we identify that a large part of the metacodes rather refer to some abstract concept of activity (e.g., action, activity type, task, work) rather than specific activities (e.g., food intake, gaming, smoking).

The 'change over time' dimension (184 meta-codes) covers some variables related to temporality (e.g., time of day, duration, period, time interval, time stamp). The remainder relates the time aspect with some other concept (e.g., asynchronicity, delay, lifetime, latency, time pressure) or a specific activity (e.g., shopping time, arrival time, production time); accordingly, the change over time of some variable is in the focus.

Remarkable is the fact that 750 meta-codes (20 percent) could not be allocated to any of the six context dimensions and had to be subsumed under 'others'. This clearly indicates that the context meta-models are incomplete and do not cover the largest part of meta-codes.

When considering data from a context meta-model perspective (Figure 2), it becomes even clearer that the context meta-models cover only a fraction of potential context variables.



Figure 2. Context dimension occurrences covered by context meta-models

The context meta-model by Schmidt et al. (1999a) shows a relatively high coverage of context variables. Chen and Kotz (2000) are also doing well with their context meta-model. Although they consider only some context dimensions, their model integrates the ones that are well described with a scale of meta-codes.

Interesting items that are not covered by existing meta-models, for instance, refer to abstract, nontangible concepts such as confidentiality, ownership, risk, threat, control, cost, easiness, simplicity, distraction, or usefulness. Other examples refer to characteristics and quality aspects such as feasibility, plausibility, efficiency, accuracy, precision, obtrusiveness, correctness, or constrainedness. Furthermore, items related to information and content (e.g., news, recommendations, content types,) are not part of existing context meta-models.

4.3 Meta-model validation: Reflection of context meta-models in pervasive computing research

While the previous section analysed the comprehensiveness of context meta-models, this section outlines how well these meta-models are reflected by research in the pervasive computing field.

For this purpose, we reviewed each of the 13 context meta-models for each context dimension. We analysed how many times (explicit and implicit occurrence frequencies) each context variable was mentioned in the article sample. In doing so, we have taken a context dimension perspective, indicating that we summed up frequencies of context variables for the respective context dimensions. The comparison matrix is provided in Table 3.

context dimensions	total occurrences	explicit occurrences	implicit occurrences	Schilit et al. (1994)	Schilit and Theimer (1994)	Rodden et al. (1998)	Schmidt et al. (1999a)	Schmidt et al. (1999b)	Chen and Kotz (2000)	Tarasewich (2003)	Bradley and Dunlop (2005)	Sitou and Spanfelner (2007)	Han et al. (2008)	Black et al. (2009)	Zainol and Nakata (2010)	Sigg et al. (2010)
physical world	3,268	3,042	226	х	х	х	х	х	х	х		х	х	х	х	X
individuals	1,370	1298	72	Х	Х		Х	Х	Х	Х	Х	Х			Х	Х
social groups	834	817	17				х						х			
activity	432	420	12				Х			х		Х		х		х
technology	1,132	1,080	52	х		х	х		х		х				х	
change over time	645	602	43		х			х	х	х		х	х			х
others	2,817	2,608	209													
covered occurrences in sample			4,370	4,283	4,287	5,636	3,883	5,015	4,315	2,502	4,315	3,447	1,832	4,370	5,542	

 Table 3.
 Context variable category occurrences matrix for context meta-models

Data reflects a wide range of context variable usage. As already mentioned in the methods section, we could identify 3,742 distinct context variables (meta-codes). These were represented by a total of 10,498 occurrences in the articles.

The most frequently considered context dimension in research practice is 'physical world' (3,268 occurrences), which is covered by almost all context meta-models. Widely discussed is also context related to 'individuals' (1,370 occurrences). Technology (1,132 occurrences) is fairly used in research practice on pervasive computing. Although 'time' and 'change over time' is included in a scale of meta-models, this category is hardly picked up in research practice (645 occurrences).

Interestingly, the 'location' – as a part of the dimension 'physical world' – has its particular significance on its own. As a separate context dimension, it would even rank three (1,287 occurrences). We may assume this high usage of location is due to its importance for mobile applications, in particular for location-based services.

Concerning the total sum of covered occurrences in the sample, the context meta-model by Schmidt et al. (1999a) is the most comprehensive one (Figure 3). Still, care has to be taken when interpreting the absolute figures per context meta-model because the number of occurrences of variables subsumed by 'others' could not be counted due to their vague definitions. Still, the model leaves out the important variable 'location', which would account for 1,287 occurrences of the calculated number of total occurrences for the model as given in Table 3.

The context meta-model by Sigg et al. (2010) also does well in covering the variables that are highly researched (5,542 occurrences). It, though, leaves out the category 'technology', which would account for additional 1,132 occurrences.



Figure 3. Number of variables per context dimension covered by context meta-models

5 Discussion

The results indicate that the scale of context meta-models with their various context categories can be narrowed down to six context dimensions. This lets conjecture that the context meta-models are quite similar. However, many of the presented context meta-models integrate only three context dimensions. For instance, the context meta-models by Han et al. (2008) (physical environment, social environment, past, present, future, and internal environment) and by Black et al. (2009) (location, objects, tasks) do not have any overlaps. Consequently, we suggest that the various context meta-models are different.

Moreover, data reveals that existing context meta-models are not comprehensive because each covers only a fraction of meta-codes while the rest of the identified meta-codes is out of scope. Although we can see that broadly defined concepts (e.g., the context dimension 'physical world') cover a wide scale of meta-codes, we would miss our target by integrating generic and broad dimensions only. While generic concepts may give a clue about what context is generally and theoretically, from a requirements engineering view, very generic concepts are insufficient. System designers find it difficult to come up with some specific idea of a concrete context variable for a specific system or application, when research provides only generic concepts on a high level of abstraction. In addition, the vast number of meta-codes found in the data demonstrates that context is a very complex construct. Accordingly, it appears almost impossible to establish a simple model that includes all thinkable variants of context variables. And be it that some researcher succeeds in doing so, it is very likely that the model's components would be so generic or abstract that they are useless to system designers. Overall, the context meta-models are well reflected in the sample, as all the models' dimensions could be met with a scale of context meta-codes. Thereby, some context dimensions are far more frequently discussed than others. For instance, the dimensions 'physical world' and 'individuals' are widely discussed, while the dimensions 'activity' and 'change over time' receive only very little mentioning. However, 27 percent of total occurrences of context variables (2,817 occurrences) could not be clearly attributed to any context meta-model. This finding reveals that research practice in pervasive computing (system development and technology advancements) is far ahead of research dedicated to model development. Moreover, this is a clear indicator that the research community does not 'stick' to existing meta-models of context when elaborating their research. Yet, in this context, it appears to be advantageous because it seems that reality has much more to offer than current meta-models express.

6 Conclusions

The context-aware and pervasive computing community has grown rapidly since the 1990's. And still it lives without a clear-cut definition of what builds the core: context. Several meta-models of context exist that postulate to frame the basis of what is understood as context.

This work compared 13 context meta-models with respect to their similarities and differences. While it could be shown that the models' categories could be narrowed down to six context dimensions, analysis also revealed strong differences because many of the context meta-models integrate only three dimensions.

Additionally, we empirically validated the context meta-models against all context variables mentioned in the Pervasive Computing Magazine in the last six and a half years. Data revealed that 20 percent of variables were not covered by any of the analyzed context meta-models.

Accordingly, there is a clear appeal to the community to dedicate efforts to basic research because the research field needs theories that reflect reality. With this paper we could demonstrate that there is much more that is context than what current context meta-models define. Furthermore, data demonstrate that pervasive computing researchers do not act upon their field's theories (context meta-models) but rather go their own way. However, the research community needs to elaborate and advance its basic theories continuously such that research practice reflects theories and theories also reflect current research endeavours. In other words, research needs to undergo a continuous process of conceptualizing context.

Against this background, future work will suggest a context meta-model that reflects research practices and integrates recent findings. The key appears to be a thorough conceptualization of context, which considers the various aspects of context information. Thereby we emphasize that the conceptualization of context is a dynamic process.

References

- Bauer, C. and Spiekermann, S. (2011). Conceptualizing context for adaptive pervasive commerce. In Proceedings of the 19th European Conference on Information Systems (ECIS 2011), Helsinki, Finland.
- Black, D. et al. (2009). Supporting the supermarket shopping experience through a context-aware shopping trolley. In Proceedings of the 21st Annual Conference of the Australian Computer-Human Interaction, p. 33-40, Melbourne, Australia.
- Bradley, N.A. and Dunlop, M.D. (2005). Toward a Multidisciplinary Model of Context to Support Context-Aware Computing. Human-Computer Interaction, 20 (4), 403-446.
- Brown, P.J. et al. (1997). Context-aware applications: from the laboratory to the marketplace. Personal Communications, 4 (5), 58-64.
- Chen, G. and Kotz, D. (2000). A survey of context-aware mobile computing research. Darmouth College, Hanover, NH.

Dey, A.K. (1998). Context-aware computing: the CyberDesk project. In Proceedings of the AAAI '98 Spring Symposium, p. 51-54, Palo Alto, California.

Dey, A.K. (2001). Understanding and using context. Personal and Ubiquitous Computing, 5 (1), 4-7.

- Dey, A.K. and Abowd, G.D. (2000). Towards a better understanding of context and contextawareness. In Proceedings of the Workshop on The What, Who, Where, When, and How of Context-Awareness, part of the 2000 Conference on Human Factors in Computing Systems (CHI 2000), The Hague, The Netherlands.
- Dobson, S. (2005). Leveraging the subtleties of location. In Proceedings of the 2005 Joint Conference on Smart Objects and Ambient Intelligence (sOc-EUSAI 2005), p. 189-193, Grenoble, France.
- Ferscha, A. et al. (2004). Context awareness for group interaction support. In Proceedings of the 2nd International Workshop on Mobility management & wireless access protocols in conjunction with International Conference on Mobile Computing and Networking (MobiWac'04), Philadelphia, PA.
- Ferscha, A. et al. (2002). Ubiquitous context sensing in wireless environments. In Kacsuk, P. et al. (eds.) Distributed and parallel systems: cluster and grid computing. Springer, New York, NY.
- Han, L. et al. (2008). Research on Context-Aware Mobile Computing. In Proceedings of the International Conference on Advanced Information Networking and Applications, GinoWan, Okinawa, Japan.
- Kolovos, D. et al. (2006). Model comparison: a foundation for model composition and model transformation testing. In Proceedings of the 1st International Workshop on Global integrated Model Management (GaMMa 2006), Shanghai, China.
- Lin, Y. et al. (2004). Model comparison: a key challenge for transformation testing and version control in model driven software development. In Proceedings of the OOPSLA Workshop on Best Practices for Model-Driven Software Development, Vancouver, Canada.
- Müller, J. and Krüger, A. (2009). MobiDiC: context adaptive digital signage with coupons. In Proceedings of the 3rd European Conference on Ambient Intelligence (AmI 09), p. 24-33, Salzburg, Austria.
- Peuquet, D. (1984). A conceptual framework and comparison of spatial data models. Cartographica, 2 (4), 66-113.
- Rodden, T. et al. (1998). Exploiting Context in HCI Design for Mobile Systems. In Proceedings of the 1st Workshop on Human Computer Interaction for Mobile Devices, Glasgow, Scotland, UK.
- Schilit, B.N. et al. (1994). Context-aware computing applications. In Proceedings of the 1st Workshop on Mobile Computing Systems and Applications (WCSA 1994), p. 85-90, Santa Cruz, CA.
- Schilit, B.N. and Theimer, M.M. (1994). Disseminating Active Map Information to Mobile Hosts. IEEE Network, 8 (5), 22-32.
- Schmidt, A. et al. (1999a). Advanced Interaction in Context. In Proceedings of the 1st International Symposium on Handheld and Ubiquitous Computing (HUC99), p. 89-101, Karlsruhe, Germany.
- Schmidt, A. et al. (1999b). There is more to Context than Location. Computers & Graphics Journal, 23 (6), 893-902.
- Sigg, S. et al. (2010). An alignment approach for context prediction tasks in UbiComp environments. Pervasive Computing, 9 (4), 90-97.
- Sitou, W. and Spanfelner, B. (2007). Towards requirements engineering for context adaptive systems. In Proceedings of the 31st Annual International Computer Software and Applications Conference (COMPSAC 2007), Beijing, China.
- Soylu, A. et al. (2009). Context and Adaptivity in Pervasive Computing Environments: Links with Software Engineering and Ontological Engineering. Journal of Software, 4 (9), 992-1013.
- Tarasewich, P. (2003). Towards a comprehensive model of context for mobile and wireless computing. In Proceedings of the Americas Conference of Information Systems (AMCIS 2003), p. 114-124, Tampa, FL.
- Weiser, M. (1991). The Computer for the 21st Century. Scientific American, 265 (3), 94-104.
- Zainol, Z. and Nakata, K. (2010). Generic Context Ontology Modelling: A Review and Framework. In Proceedings of the 2nd International Conference on Computer Technology and Development (ICCTD 2010), p. 126-130, Cairo, Egypt.