12-2013

Relational Model Bases: A Technical Approach to Real-time Business Intelligence and Decision Making

Elizabeth White Baker

Wake Forest University, bakerew@wfu.edu

Follow this and additional works at: <https://aisel.aisnet.org/cais>

Recommended Citation

Baker, Elizabeth White (2013) "Relational Model Bases: A Technical Approach to Real-time Business Intelligence and Decision Making," *Communications of the Association for Information Systems*: Vol. 33 , Article 23.

DOI: 10.17705/1CAIS.03323

Available at: <https://aisel.aisnet.org/cais/vol33/iss1/23>

This material is brought to you by the AIS Journals at AIS Electronic Library (AISeL). It has been accepted for inclusion in Communications of the Association for Information Systems by an authorized administrator of AIS Electronic Library (AISeL). For more information, please contact elibrary@aisnet.org.

Communications of the Association for Information Systems

Relational Model Bases: A Technical Approach to Real-time Business Intelligence and Decision Making

Elizabeth White Baker

Schools of Business, Wake Forest University

bakerew@wfu.edu

Abstract:

This article presents a technical approach to acquiring quality, real-time decision-making information within organizations and illustrates this approach with an extended case study. Using relational model bases for real-time, operational decision making in organizations facilitates a transition to dynamic (vs. forecast-driven) resource allocation decisions. These and related systems offer development of a new generation of DSS applications which can be applied to extend preemptive decision making across many industries. This approach is illustrated through a description of a detailed conceptual case (scenario) pertaining to its application in agribusiness. This approach to decision making can be viewed as an extension of well-known techniques pertaining to DSS but also represents the opportunity to address problems not amenable to traditional post hoc analysis. Researchers can learn from the accumulated knowledge pertaining to DSS but can also examine innovations that push forward into new territories. The article presents and discusses a variety of emergent research questions prompted by the application of these technologies in the business environment.

Keywords: organization, decision support systems, real time, business intelligence, relational model base

Editor's Note: The article was handled by the Department Editor for Special Section on Emerging Ideas and Topics in IS

Volume 33, Article 23, pp. 393-406, December 2013

The manuscript was received 05/15/2012 and was with the authors 6 months for 2 revisions.

I. INTRODUCTION

The development and deployment of RFID sensors, massive Web-based data (e.g., network traffic, user clicks, etc.) and many other new sources of streaming data offer many operational opportunities for industries as diverse as supply chain management and health care. The prevalent model of DSS would integrate incoming data with other organizational information largely for the detection of patterns and to aid in long-range decision making. This will continue to be an important and profitable function of DSS.

However, achieving full value from these streams of data requires new organizational approaches to fully utilize them in predictable and innovative ways [Niederman, Mathieu, Morley and Kwon, 2007]. Although one approach to using this data involves traditional storage and analysis, it has been argued that additional uses are conceivable that will take better advantage of the real-time processing of the enormous volume, velocity, and variety of data that these sources make available [McAfee and Brynjolfsson, 2012]. This approach focuses on automated analysis of data as it arrives rather than post hoc analysis after operational activities have been completed. Such a priori processing offers an approach to address competitive situations that require actionable information much more rapidly than ever before, minimizing lengthy (or impossibly complex) processing. From a strategic perspective, firms are challenged to ensure the real-time availability, agility, and adaptability of information, both internally and externally, required for handling dynamically changing business and competitive environments [Pralhad, 2009; Kohli and Grover, 2008; Sambamurthy, Anandhi and Grover, 2003; Mithas, Ramasubbu and Sambamurthy, 2011]. The ability to develop more flexible operational responses during the processing of transactions can represent a strategic approach or advantage relative to firms without that level of flexibility. Tesco, a bricks-and-mortar UK grocer, gathers transaction data on its 10 million customers and uses the information to analyze new business opportunities—for example, how to create the most effective promotions for specific customer segments. They further apply data to inform their strategic direction using data to inform decisions on pricing promotions and shelf allocation. Fresh Direct, a U.S. online grocer, shrinks reaction times even further to adjust prices and promotions daily or even more frequently, based on data feeds from online transactions, visits by customers to its website, and customer service interactions. In healthcare the University of Ontario Institute of Technology and Toronto's Hospital for Sick Children use real-time data collected from premature infants in its nursery to detect earlier hospital-acquired infections in these infants, enabling the children to be treated before the situation becomes life-threatening [Baluja, 2012].

One approach to such automated decision processing is real-time processing which can be expected to make available the most current data upon which to base business intelligence [Duan and Xu, 2012; Watson and Wixom, 2007]. The current approach to enacting real-time processing uses active data warehouses and push-based BI (made possible with the arrival of large quantities of addressable RAM). Using underlying technologies such as complex event processing and event correlation, operational intelligence analytics are a step in the direction of finding and extracting information before it heads into the data warehouse, where the time to retrieve the information again increases significantly. Operational intelligence allows for operational data that does not need to be loaded into the warehouse before analysis, as the arrival of events in the data input stream triggers processing of the query.

However, even with the application of these techniques, organizations are still reliant on fixed models. To achieve true real-time BI systems need to “learn” or adapt from the data being streamed in during the data acquisition stage to update and/or replace decision models [Blei, 2012; Chandy and Schulte, 2010; Marjanovic, 2007]. Once instantiated, these complex, adaptive systems would take streaming data and allow for algorithmic data decision-making interaction.

One promising approach to moving toward such “true” real-time processing may be based on the use of model bases to process the data [Davenport and Harris, 2005]. As an active, model-driven DSS class [Power, 2008], relational model bases address transaction and process automation with internal, integrated processes when deployed as an organizational decision support system (ODSS) [Carter, 1992; Eom, 2007; George, 1992] and has the potential to be deployed to support transaction and process automation with inter-organizational (peer) processes when deployed as an inter-organizational system (IOS) [George, Nunamaker and Valacich, 1992; Sen,

Moore and Hess, 2000].¹ Cohen, Kelly and Medaglia [2001] describe several implementations of optimization-based DSS that integrate data from several sources, signaling model-based DSS as finally poised to emerge as a powerful tool for organizational decision making.

Relational model bases exist today in very basic instantiations where models can be changed only manually. Conceptually, relational model bases are an emerging technology that would allow input data to add, update, or delete aspects of the *models* upon which input data is processed autonomously, in addition to being able to alter the parameters of the model. A relational model-base structure as a class of active, adaptive DSS [Holsapple, Pakath, Jacob and Zaveri, 1993; Jacob and Pirkul, 1990; Manheim, 1989; Mirchandani and Pakath, 1999] acts as an integrative device by relating an organization's elementary relational functions to each other in models prior to data acquisition with a model management system at its core to build, analyze, and maintain models *dynamically as the system inputs and elementary relational functions evolve* [Liu and Tuzhilin, 2008; Muhanna and Pick, 1994]. Sutherland and Baker [2007] show that relational model bases can provide the technical capability for encouraging constructive interconnections among decision models in the overarching process of providing more adequate and accurate real-time, decision-making information.

It is important to keep in mind that while relational model bases provide an opportunity to provide value by capturing and exploiting real-time data for decision making and action taking, they are not likely to be as successful if applied to inappropriate tasks. Appropriate tasks must involve situations with regular decision instances, when the decisions are recurrent and routine. The decision task must also admit to a conventional, technical, algorithm-driven solution for which decision choices are deterministic or probabilistic in nature. In organizations where a premium is placed on real-time propositional decision functions and near-instantaneous decision execution, instantiations of relational model-base structures would serve to provide these organizations with a mechanism to analyze the propositional decision functions in *real time*. Proctor and Gamble uses real-time data to monitor conditions so that if supplies are delayed due to weather, traffic, or other causes, the systems will use the data to create alternative delivery scheduled to ensure that production facilities get the appropriate supplies in sufficient quantities [O'Leary, 2008]. Real-time data in healthcare can help clinical decision making at the individual level and the population level by interpreting and monitoring patient data for diagnosis, establishing benchmarks and alerts to help with chronic disease management, and detecting pandemic diseases or tracking chronic diseases, aiding overall public health surveillance [Basu, Archer and Mukherjee, 2012].

This work addresses an open research question in the domain of real-time business intelligence [Ranjan, 2008]. A gap exists in this research regarding tools that would allow for the real-time synthesis of data *prior* to processing into a warehouse for decision makers, either solitary decision makers or groups charged with making a decision. This research path is taken in response to a plea made by several IS researchers concerned that this area might be overlooked by the IS field at a critical moment during this intense focus on "Big Data" and its potential impacts [Chen, 2011; Chen, Chiang and Storey, 2012]. This research also addresses the industry need to shorten the time lag between data acquisition and decision making [Chaudhuri, Dayal and Narasayya, 2011]. The research question addressed is: What are the technical requirements when an information system must process information prior to its being stored in the data warehouse, delivering output that is algorithmic to make automated decisions, or easily interpretable by a human decision maker for real-time decision making?

Relational model-base structures are presented in the following section, followed by a discussion of the potential impacts of IS research that could be done in this area throughout several knowledge domains. One approach to responding to this challenge of implementing such a system will be presented based on a case within the field of precision agriculture. Precision agriculture is the field of whole-farm management with the goal of optimizing returns on inputs (economics) while preserving resources (environmental conservation) by matching farming practices more closely to crop needs (crop science). The exemplar relational model base is applied to precision farming, a farming management concept based on observing and responding to intra-field variations. The article concludes with a discussion of additional areas to which this technical solution could be applied and the potential impact of the widespread adoption of these systems in organizations.

¹ Relational model bases are not to be confused with relational database management systems (RDBMS). In RDBMS, decision models can be built, but their processing does not vary dynamically based on the input data as it is processed. Of course, a technologist can reprogram the decision models within the RDBMS; however, such reprogramming will be inefficient (e.g., requiring scheduled human labor) and will invoke a delay (e.g., finding the need to reprogram, taking the time to change the model, testing the new design, and running the new model).

II. RELATIONAL MODEL-BASE STRUCTURES: A RECURSIVE APPLICATION IN PRECISION AGRICULTURE

Agriculture is one commercial endeavor where there is a clearly identified need to improve operational efficiencies by integrating processes between participants at various levels [Henderson, Akridge and Dooley, 2006; Ernst and Tucker, 2002]. Additionally, the need for real-time information processing to facilitate more efficient agricultural decision making, including the introduction of more sophisticated decision technologies, also has been identified [Diekmann and Batte, 2010; Hirafuji, 2000; Massey, Myers, Kitchen and Sudduth, 2008; Schiefer, 2003]. As an industry in the U.S. alone, agribusiness is a 2.4 trillion USD industry with an annual growth rate of 1.5 percent [Kruchkin, 2012]. Precision agriculture systems and services, a subset of the agribusiness industry, has U.S. revenue of 1.3 billion USD with annual growth projected at 6.1 percent [McBee, 2012]. The robust growth rate reflects that technological innovations within precision agriculture systems will make the technology more compelling to implement, in spite of farmers' general lack of technological sophistication as a group [Kitchen, Snyder, Franzen and Wiebold, 2002; Omid-Najafabadi and Bahramnejad, 2010]. The adoption and diffusion of precision agriculture will increase as penetration of broadband and mobile technologies in rural areas grows and educational efforts achieve further success [Kitchen, 2008; Lamb, Frazier and Adams, 2008]. Worldwide, the growing demand for agriculture products and services from newly industrialized countries will make the use of precision agriculture more attractive [Omid-Najafabadi, Hosseini and Bahramnejad, 2011].

More importantly than market size, precision agriculture is a clear example of how relational model bases can be used to improve sustainability in the global food supply [Walsh et al., 2006] and improve farmers' profitability [Rickman et al., 2003], encouraging a more rapid adoption of the technologies. Having these precision agriculture technologies contribute to the sustainability of agricultural systems stressed by increasing food and biofuel demands is a critical humanitarian issue. Population growth is expected to increase, and world population is projected to reach 10 billion by 2050. This population growth decreases per capita arable land. More intensive agricultural production will have to meet the increasing food demands for this increasing population, especially because of an increasing demand for land area to be used for biofuels [Delgado and Berry, 2008; McConnell and Burger, 2011].

This case is developed in the context of agribusiness, with the target application being precision agriculture, alternatively known as precision farming. The goal of precision agriculture is to retain the benefits of large-scale mechanization essential to the large fields (many kilometers square is typical of today's farm sites), while recognizing local variation within the large field site, both made possible through the increased use of technology. As rationale for introducing relational model bases to aid in this case, it is important to note how the geographical scale of these decision requirements has increased dramatically for today's farmer. In the United States, a farm operator now manages a square mile or more to be viable, with the size of a typical field measuring hundreds of meters on a side. Usually all portions of that large farmland plot are treated similarly, with crop varieties, seed density, soil preparation, fertilizers, and insecticides (among other chemical treatments) uniformly applied [Rickman et al., 2003]. However, grain crops respond to environmental and soil variables that vary on subfield scales, especially as the farm fields get larger in acreage. To minimize the amount of production lost due to the mismatch of uniform crop treatments and unique physiological responses of individual plants in the crop, the ability to farm more precisely and apply decision requirements for all the associated crop variables on a smaller scale within the farm would be advantageous. Additionally, this associated increase in the scale of geographical decision requirements for precision agriculture has corresponded to a decrease in the response time available for farmers to be able to make these decisions, further highlighting the need for an integrative system to optimize and expedite decision making.

The introduction of relational model bases to this scenario is of tremendous benefit to the practice of precision agriculture, as the computational requirements for decision making in precision agriculture are high in deciding specific amounts and combinations of seeding, fertilizer, chemical, and water use for local variations of the large land plots, while the required response time is short, to make certain that the land is optimally planted relatively quickly over ever-larger scales. The benefits of applying real-time BI to precision farming also include the integration in real time of decision models by the relational model base, allowing the farmer to invest decision authority in the model-base system, freeing the farmer to make more strategic decisions about his operation, while simultaneously gaining the capability to more quickly and accurately process the decision inputs acquired to make the decisions. A diagram of a generic prototypical relational model-base-centered integrative system appears in Figure 1.

In this generalized conceptual case, the relational model-base-centered integrative system is going to be detailed from the perspective of a grain producer, including specific requirements for a relational model-base system in this environment. The outline of this article is as follows: after the relational model-base-centered integrative system for the grain producer is detailed, based on Figure 1, the relational model-based structures will be outlined, followed by a discussion of how large quantities of inputs to create and modify models would be handled by this system. This

Figure 1. A Prototypical Relational Model-base-centered Integrative System

article concludes with a discussion of possibilities and implications of relational model base implementation in the enterprise.

III. A GRAIN PRODUCER'S RELATIONAL MODEL BASE AND ITS CHARACTERISTICS

Within the context of precision agriculture and from the perspective of a grain producer, the target application of this integrative system is stewardship over the determination of the amount and placement of a particular crop to be grown on a farm plot (or the combination of crops and in what amount) and the associated amounts of seeding, soil nutrient, pesticides, and moisture levels for the given crop, all of which comprise the decision requirements. Figure 2 shows what a relational model-base structure would look like in a real-time, decision-making system applied to precision farming.

Figure 2. A Relational Model Base Model with an Example from Agribusiness

In addition to knowing the target application and the decision requirements in the relational model-base-centered integrative system, grain farming comes with an inherent structural model consisting of connective (structural) specifications and substantive (magnitudinal) determinant-level specifications. Connective specifications indicate which state variables are interlinked with which others in what ways. In a real-world precision agriculture situation, the complex interplay among decision models governing nutrient absorption, thermal emission of the plants, water absorption, and necessary rates of irrigation with relation to precipitation form the connective specifications in precision farming. An example of the complexity of one model involved is presented in Kim, Sudduth and Hummel [2009], who model soil macronutrient sensing for precision agriculture.

For each particular farm, there would also be substantive specifications, which are the results of the calculation of the initial parameters and relationships/constraints relating nutrient, crop, and water decisions. These initial substantive (magnitudinal) specifications would be the initial parameters (b_x) and relational coefficients (m_x) that would inform the grain producer's relational model-base structure in a real-world example. For the purposes of a vastly simplified illustrative example, in Table 1, we chose four variables relevant to grain farming planting decisions and outline their connective and substantive specifications, which together comprise the inherited structural model for the relational model base.

A relational model-base structure for a grain producer would also have very specific information acquisition requirements to be able to provide decision makers with adequate accurate and current decision predicates. These requirements would involve the determination or collection of any relevant empirical data necessary to calculate the relational model-base substructure parameters and relational coefficients. On a modern farm, there are several specific pieces of information that need to be known for effective decision making; thus information acquisition requirements would include (among others) temperature and composition of the soil, weather conditions on the site, fertilizer residue present in the soil, and moisture conditions of the soil. Knowing the requisite information acquisition requirements in precision farming for the development of more current and accurate data collection directs the ability to tap the appropriate real-time data sources.

The data sources from which the relational model base for the grain producer would gather its information in the precision farming environment will be empirical data (sampling-based) from field observations recording the current parameter values for many variables of interest. In the move toward more real-time decision making, it is in this area where precision farming has made the greatest gains thus far [Rickman et al., 2003]. Improved navigation equipment, yield monitors, soil sensors, weather equipment, satellite and cellular network communications, etc., can all be used in a more sophisticated manner to provide decision makers (or technical decision aids, such as relational

Table 1: Inherited Structural Model and Substructure for Agribusiness Example

	Inherited structural model	Relational model-base substructure
Variables	v_1 : the amount of seed that is planted v_2 : the amount of irrigation necessary to achieve optimal soil moisture v_3 : the amount of pesticide used v_4 : the amount of fertilizer used	
Connective specifications (elementary relational operators)	v_2 is $\uparrow$ (positively and proportionally) related to v_1 v_3 is $\uparrow$ (positively and proportionally) related to v_1 v_4 is $\uparrow$ (positively and proportionally) related to v_1 v_2 is $\Rightarrow$ (dependent on (dominated by)) level of current soil moisture, s_o	$r_x(1 \cap 2)$: v_2 is $\uparrow$ (positively and proportionally) related to v_1 $r_x(1 \cap 3)$: v_3 is $\uparrow$ (positively and proportionally) related to v_1 $r_x(1 \cap 4)$: v_4 is $\uparrow$ (positively and proportionally) related to v_1 $r_x(2 \cap 3)$: v_2 is $\uparrow$ (positively and proportionally) related to v_3 $r_x(2 \cap 4)$: v_2 is $\uparrow$ (positively and proportionally) related to v_4 $r_x(3 \cap 4)$: v_3 is $\uparrow$ (positively and proportionally) related to v_4
Substantive specifications (computational functional relationships)	$v_2 = m_2v_1 + s_o + b_2$ $v_3 = m_3v_1 + b_3$ $v_4 = m_4v_1 + b_4$	

model-base substructures) with almost instantaneous readings of soil temperature, moisture, precipitation, and pesticide levels, along with any other parametric direct measurement variables that might be of interest [Kitchen, 2008]. Farmers currently use wireless, high-speed Internet services, and other forms of wireless, networked communications to link various sensors or grids of sensors placed throughout their vast farm areas to get readings on crop moisture, temperature, weather, soil composition, and field conditions, among other things [Hirafuji, 2000; Ninomiya, 2004; Rickman et al., 2003]. By having these grids of sensors provide real-time readings of the state of farm conditions, the most current and accurate empirical data can be provided to a relational model-base substructure for decision support.

With the copious amounts of data that will be collected from the field observations and conditions factors, it will be necessary to employ some means of input fusion to reduce the total aggregate of data collected down to the smallest actionable amount. Various methods of data reduction could be used, including collation, aggregation, redundancy filtering, and templating. In this agricultural case, various spatial-compilation algorithms, such as GPS correction, would be employed for crop-sensor data, as well as correction algorithms for raw yield data, and antenna offsets correction. Each of these input fusion techniques would lead to the eventual output of current values for parameters and relational coefficients of the relational model base.

The Relational Model-base Structure

The structure of the relational model-base system itself within the recursive relational model-base-centered integrative system will be explicated in detail in this section. All aspects of the integrative system from discussion of the target application and its decision requirements through to the empirical data collection and input fusion leads to the structure of the relational model-base system itself. As the graphic in Figure 2 depicts, the relational model-base system consists of five interrelated parts: the relational model-base structure; the cellular-connectionist analysis and modeling conventions, for systematically recognizing and formulating relational constructs in the relational model-base; computational decision tree constructs; the initial substantive specifications of the relational model-base structure consisting of the current values for parameters and relational coefficients (as shown in Table 1 earlier in this article as an illustrative example); and, finally, updating operations to continuously update the parameters and relational coefficients of the relational model-base structure based on continuously streaming empirical data from field observations. Each of these five pieces together forms the comprehensive relational model-base structure central to the relational model-base-centered integrative system.

The cellular-connectionist analysis and modeling conventions in the case of the grain producer, independent of a grain miller, is the necessary beginning of the relational model-base structure. The relational operations in this case build to first-order (inter-decision) operations, allowing for task- and entity-independent links between decisions. As shown in Table 1, at the elementary relational operator level, $r_x(v_m \cap v_n) \in d_x$, there are codified links among variables that are related to planting one particular grain (from here on referred to as the planting decision model,

(d_x): amount of seed that is planted (v_1); the amount of irrigation (v_2); the amount of pesticide used (v_3); and the amount of fertilizer used (v_4). (In a real-world example, there would be many other variables that are relevant to this decision, yet for the sake of simplicity, the number of variables in this illustrative example is going to be limited to four.) The relational operators (r) among these variables constitute the decision model for planting, d_x , where $d_x = R(v_1 \cup v_2 \cup v_3 \cup v_4)$, which is detailed in Table 1 as the substantive specifications, and R is a primary relational operator conjoining the elementary relational operators, consisting of the system of equations in the illustrative example. For the remainder of this discussion, $r_x(v_m \cap v_n)$ will be abbreviated $r_x(v_m, v_n)$.

Returning to the computational constructs for this model, this hierarchical decision case assumes dependent or co-dependent decision-making relationships in the organization that relate to each other and to other participants in the supply chain who might govern what is being farmed and in what quantity. These decision-making relationships are hierarchical and recursive in nature, with the mathematical constructs informing the relational model-base structure operationalizing as a system of linear equations in a hierarchical node-arc structure, where the nodes contain executable decision models (algorithmic objects) and the arcs hold relational functions that explicate any connections between or among the various nodal objects.

Table 2: Relational Model-Base Substructures' Configuration Features for Planting Decision Model (d_x)

	Relational Substructure $R(d_x)$			
	$v_1 = v_{1,t-1}$	$v_2 = v_{2,t-1}$	$v_3 = v_{3,t-1}$	$v_4 = v_{4,t-1}$
$v_1 = v_{1,t}$	ϕv_1	$f(1,2) = f(2,1)$	$f(1,3) = f(3,1)$	$f(1,4) = f(4,1)$
$v_2 = v_{2,t}$	$f(2,1): v_2 = m_2 v_1 + s_0 + b_2$	ϕv_2	$f(2,3) = f(3,2)$	$f(2,4) = f(4,2)$
$v_3 = v_{3,t}$	$f(3,1): v_3 = m_3 v_1 + b_3$	$f(3,2): v_3 = m_3((v_2 - b_2)/m_2) + b_3$	ϕv_3	$f(3,4) = f(4,3)$
$v_4 = v_{4,t}$	$f(4,1): v_4 = m_4 v_1 + b_4$	$f(4,2): v_4 = m_4((v_2 - b_2)/m_2) + b_4$	$f(4,3): v_4 = m_4((v_2 - b_2)/m_2) + b_4$	ϕv_4

Table 2 shows a relational substructure of d_x , which in this case is the decision model for planting. Across the top of the grid is the current parameter value for each variable (v_m), which would be initially determined or calculated by empirical field data and over time would be updated through direct observations or through Bayesian updating operations to incorporate new information acquisition data weighting the most recent observations more heavily than older ones. Each row consists of a variable pertinent to the decision model, in this case, v_1 , v_2 , v_3 , and v_4 . Where the rows and columns intersect, there is the elementary relational operator, which describes the character and magnitude of the actual or anticipated impact of the current value on that variable. In the case of the grain producer, $r_x(v_2, v_1)$ would signify the relationship/effect of the amount of irrigation (v_2) on the amount of a particular seed that is planted (v_1), which is $r_x(v_2, v_1) = v_2$ is $\uparrow$ (positively and proportionally) related to v_1 . The value v_1 at the top of the column would be the current amount of that seed that is being planted, and the value would be updated over time. In this illustrative example, v_1 is the value of variable v_1 at time ($t-1$). Based on the substantive specifications, $r_x(v_2, v_1)$ would be replaced by a mathematical or algorithmic expression, $f(2,1)$, where the categorical connectives would be expressed by a mathematical function, as shown for this illustrative case in Table 2.

In a time series example, ϕv_1 describes the relationship between v_1 and v_1 at time t . It is used to compute the value of v_1 at time t based on the value of v_1 at time ($t-1$), which is v_1 . ϕv_1 is not defined algorithmically in this current example, as the value of v_1 and v_1 are not related computationally. The value for v_1 at any given time is based on GPS input function data describing the planting terrain. As the farmer plants and navigates throughout his or her field, differing GPS coordinates processed through a planting map will give the farmer different values for the amount of seed to be planted, based on his or her location in the field. The functions ϕv_2 , ϕv_3 , and ϕv_4 also are not defined algorithmically in this particular example. Overall, in a real-world example, the entire relational model-base structure, consisting of all the interconnected substructures, would be filled out by all of the variables that had been identified in the cellular-connectionist analysis, reflecting all pertinent relationships in the planting decision model, d_x .

Table 3: Relational Model-base Output for Planting Decision Model (d_x)

	(m2 = 2; m3 = 0.1; m4 = 0.3; b2, b3 and b4 = 0)			
	v_1	v_2	v_3	v_4
t = 0	10	20	1	3
t = 1	20	40	2	6
t = 2	5	10	0.5	1.5
t = 3	10	20	1	3

After all of the data has been processed through the decision-driven relational model-base structure, the current decision predicates (the actual values for v_1 , v_2 , v_3 , v_4) would be available in real time for the grain producer. Table 3 shows the actual values for running the relational model base for the illustrative example, assuming that for each 10

pounds of seed planted, a farmer needs 20 cubic feet of water, 1 pound of pesticide and 3 pounds of fertilizer. At each time t , the amount of seed to be planted is fed into the relational model base from the data sensors, determined based on the GPS position of the farm plot being planted; subsequently, the model calculates the remaining variables in the model. In real-world precision farming, every acre of land would have readings of the input variables taken in real-time from remote wireless sensors and satellite data streams as the turbine/tractor covers the ground distributing the seed and tailored mixture of P, N, and K. With the large size of such farms (tens of thousands of meters) and the pace with which this farm equipment must cover such plots for the optimal farming output, real-time processing is needed to determine the outputs from the large volume of inputs and the decision models that are employed.

Considering that agriculture is a largely geographical endeavor, some GIS-based construct would be used as the interface where all decision predicates would be displayed to the decision maker in a format that displays the density or frequency distribution data of relevant variables as mapped onto the grain producer's farm production area. As a final piece of the recursive relational model-base-centered integrative system, information acquired from the resource disposition decisions made, which consists of current parameter values resulting from the decision execution, is fed back into the relational model-base structure. This data would be stored outside of the relational model-base structure itself. The quality of previous decisions would be assessed based on different inputs and the outcomes effected [Jones and Taylor, 2004].

The key aspect of relational model bases that make them a new type of DSS is that this quality assessment could subsequently be used to generate better decision models *in real time*, in collusion with the incoming data acquisition requirements, acquired from RFID sensor arrays, for example. Armed with this information, updating operations would be used to update the relations between the variables (model, or substantive specifications, updating), while Bayesian updating operations would update present operating values for parameters and relational coefficients, examples of which are shown in Table 3. Model specification updating functions, which are ideally dynamic and agent-based in operation, would serve to enact model updating within the relational model-base structure in the likely event that new data force a significant enough change in the value of a variable that a model alteration or outright substitution that would affect changes in all other variables subject to the original variable's influence." How parameters and models are updated in a relational model-base structure is shown in Figure 3.

Figure 3. Dynamic Parameter and Model Updating Functions in a Relational Model Base

IV. ECONOMIC IMPLICATIONS

The goal of the enterprise is to establish optimal profit margins for the organization. For probabilistic decisions where the decision maker is risk averse, such as those present in precision agriculture, improvements in the quality of an

information base in terms of richness, precision, credibility, and/or currency result in a favorable change in the structure of the associated probability distribution, as shown in Figure 4.

The distribution in Figure 4a, driven by an improved information base provided by the relational model-base structure, with its updating operations for model specification and parameter updating, entails a lower expected value of the decision error than the distribution in Figure 4a, which is based on a less complete information base. In both distributions, μ is taken as the amount of grain that needs to be provided by the grain producer to satisfy the completed bid with the grain miller. The key difference between the two distributions is Figure 4b's much narrower range of production values that are deemed possible. This contraction is presumed to be a consequence of additional valuable information contained in the underlying information base of Figure 4b. This results in a reduction in the expected value of decision error (EVDE), defined as the probability multiplied by loss for all $|\mu - \alpha|$, where α is any value included in the range of the probability function.

The distribution in Figure 4b has a lower EVDE than that in Figure 4a because the worst that is expected to happen is that there would be a loss (real or opportunity) of 1000 (vs. 5000) units. Thus, the value of information from the relational model base that is seen as an improvement over information provided from current systems is equal to the EVDE (area in Figure 4a—area in Figure 4b). Thus, to the extent that the relational model-base structure on any level can provide an improved information base that will reduce the EVDE and provide tightening and elimination of bias in the mean, moving to a relational model-base structure to facilitate organizational decision making is valuable to any organization that implements it. Over time, the investment in the system will generate positive returns stemming from this improved decision making.

V. DISCUSSION

Relational model-base structures are most well-suited to scenarios in which the decision outcomes are reasonably well-bounded. The decision makers in the organization cannot be reasonably expected to meet the data processing demands that a high response, real-time situation requires; therefore, these decision makers turn to inter-organizational, real-time, multi-criteria, multi-decision-making tools that can provide this capability. Therefore, the potential for these relational model base systems includes any decision-making scenario where real-time business intelligence is needed and where there is value in automating the decision making to provide this real-time data, providing a tool with the capability to solve many complex problems in several knowledge domains. These areas include public health and emergency services (i.e., pandemic response plans), bioinformatics, customer segmentation, and inventory management, in addition to the more widely recognized areas of fraud detection, risk management, financial modeling, and trade execution [Kloeckl, Senn and Ratti, 2012; Lederman and Wynter, 2011; Livengood, Maciejewski, Wei and Ebert, 2012; Maciejewski et al., 2011].

The case for the introduction of relational model bases is further strengthened by the fact that there already exist cases where propositional decision-function data goes into models and is processed in real time when response requirements in the situation are high. A representative example in finance is ActivePivot (quartetfs.com), a real time

risk assessment tool for credit, market, counterparty, or liquidity risk, and an example in pandemic preparedness and public health is BioDiaspora (www.biodiaspora.com), a research project focused on the health implications of global population mobility. Although any of these scenarios could be chosen for investigation, this work looks in depth at a case in precision agriculture, detailing the appropriate conceptual model of the relational model base applied to this situation and discussing how this relational model base is reflected in the industry solution for real-time BI. Industry has developed relational model-base systems for use in precision agriculture and ecological reclamation projects, without those systems being termed as such. By looking at the work of those in industry who have deployed such solutions (e.g., IDLAMS (Integrated Dynamic Landscape Analysis and Modeling System) [Shoemaker, Dai and Koenig, 2005]), we can reevaluate and reposition the prior IS literature on real-time BI DSS to approach the problems we are encountering now that can be addressed by relational model bases.

VI. CONCLUSION

This work addresses an open research question regarding tools that enable the real-time synthesis of data *prior* to processing into a warehouse for decision makers, either solitary decision makers or groups charged with making a decision. This research path is taken in response to a plea made by several IS researchers concerned that this area might be overlooked by the IS field at a critical moment during this intense focus on “Big Data” and its potential impacts [Chen, 2011; Chen, Chiang and Storey, 2012]. The conceptual case presented is designed to illustrate how a relational model-base approach can address the opportunity presented by the explosion of data inputs and the need for dynamic models for real-time decision-making data. This work focuses on the technical requirements for implementing such a decision tool in an organizational setting. As the case is hypothetical, we would expect to learn more in the dialogue between technology constraints and organizational facts. Naturally much work remains in order to translate such a conceptualization into institutionalized everyday processes for placing these technologies regularly into business contexts.

In our view there are a number of directions for the extension of knowledge regarding this sort of technology. First, from a more technical perspective, the principles and examples described herein can (and likely will) be replaced over time with more specific and detailed sets of specifications. An accumulation of knowledge that distinguish more from less helpful approaches will ultimately save time from repeated trials and false starts. Second, from an organizational perspective, the range of tasks and the variations of technology required for successful implementation are not clear. Optimally tasks that are important, repetitive, and describable in models will be the “low hanging fruit,” but how far can such tasks be pushed into the less repetitive, more complex, and even more quickly changing models? Third, from an historic perspective, contrasting both content and methods of development useful in DSS applications with those in the emerging relational model-base world can provide some basis for more quickly reacting to the next steps forward in decision-making technologies.

In the view of many, there is a Big Data revolution occurring where the growth of technology is leading to a deluge of decision-making data, while rapidly changing competitive environments demand business intelligence derived from this data to be available and applied in real time. Using relational model bases as a more sophisticated real-time, operational decision making in organizations in order to aid the transition to dynamic (vs. forecast-driven) resource-allocation decisions, relational model bases can and are leading to a new generation of DSS applications in fields ranging from bioinformatics and agriculture to supply chain management and personalized marketing. This is the beginning of a new set of technical and behavioral research questions where IS researchers can seize the moment and make a significant impact on many knowledge domains, including the grand challenges of IS and engineering [Chen, 2011; National Academy of Engineering, 2008].

ACKNOWLEDGMENTS

The author would like to gratefully acknowledge the helpful comments of the reviewers and associate editor of this article.

REFERENCES

Editor's Note: The following reference list contains hyperlinks to World Wide Web pages. Readers who have the ability to access the Web directly from their word processor or are reading the article on the Web, can gain direct access to these linked references. Readers are warned, however, that:

1. These links existed as of the date of publication but are not guaranteed to be working thereafter.
2. The contents of Web pages may change over time. Where version information is provided in the References, different versions may not contain the information or the conclusions referenced.
3. The author(s) of the Web pages, not AIS, is (are) responsible for the accuracy of their content.
4. The author(s) of this article, not AIS, is (are) responsible for the accuracy of the URL and version information.

- Baluja, T. (2012) "Technology Detects Infections Before Doctors Know Preemies Are Sick", *The Globe and Mail*, August 12, sec. Life, Health and Fitness, <http://www.theglobeandmail.com/life/health-and-fitness/health/technology-detects-infections-before-doctors-know-preemies-are-sick/article4473808/> (current Mar. 22, 2013).
- Basu, R., N. Archer and B. Mukherjee (2012) "Intelligent Decision Support in Healthcare", *Analytics Magazine*, <http://www.analytics-magazine.org/januaryfebruary-2012/507-intelligent-decision-support-in-healthcare> (current Mar. 22, 2013).
- Blei, D.M. (2012) "Probabilistic Topic Models", *Communications of the ACM*, (55)4, pp. 77–84.
- Carter, G.M. (1992) *Building Organizational Decision Support Systems*, Boston, MA: Academic Press.
- Chandy, K.M. and W.R. Schulte (2010) *Event Processing : Designing IT Systems for Agile Companies*, New York, NY: McGraw Hill.
- Chaudhuri, S., U. Dayal and V. Narasayya (2011) "An Overview of Business Intelligence Technology", *Communications of the ACM*, (54)8, pp. 88–98.
- Chen, H. (2011) "Design Science, Grand Challenges, and Societal Impacts", *ACM Transactions on Management Information Systems*, (2)1, pp. 1–10.
- Chen, H., R. Chiang and V. Storey (2012) "Business Intelligence and Analytics: From Big Data to Big Impact", *MIS Quarterly*, (36)4, pp. 1165–1188.
- Cohen, M.-D., C. Kelly and A.L. Medaglia (2001) "Decision Support with Web-enabled Software", *Interfaces*, (31)2, pp. 109–129.
- Davenport, T. and J. Harris (2005) "Automated Decision-making Comes of Age", *Sloan Management Review*, (46)4, pp. 83–89.
- Delgado, J.A. and J.K. Berry (2008) "Advances in Precision Conservation", *Advances in Agronomy*, (98), pp. 1–44.
- Diekmann, F. and M. Batte (2010) "2010 Ohio Farming Practices Survey: Adoption and Use of Precision Farming Technology in Ohio", AEDE-RP-0129-10, *Agricultural, Environmental and Development Economics*, College of Food, Agricultural and Environmental Sciences, Columbus, OH: The Ohio State University Extension.
- Duan, L. and L.-D. Xu (2012) "Business Intelligence for Enterprise Systems: A Survey", *IEEE Transactions on Industrial Informatics*, (8)3, pp. 679–687.
- Eom, S.B. (2007) *The Development of Decision Support Systems Research : A Bibliometrical Approach*, Lewiston, NY: Edwin Mellen Press.
- Ernst, S.C. and M. Tucker (2002) "'Agri-culture': A New Look at Adoption and Diffusion of Information Technology", Presentation at International Meeting of Agricultural Communicators in Education, Savannah, GA.
- George, J.F. (1992) "The Conceptualization and Development of Organizational Decision Support Systems", *Journal of Management Information Systems*, (8)3, pp. 109–126.
- George, J.F., J.F. Nunamaker and J.S. Valacich (1992) "Information Technology for Organizational Change", *Decision Support Systems*, (8)4, pp. 307–315.
- Henderson, J.R., J.T. Akridge and F.J. Dooley (2006) "Internet and e-Commerce Use by Agribusiness Firms: 2004", *Journal of Agribusiness*, (24)1, pp. 17–39.
- Hirafuji, M. (2000) "Creating Comfortable, Amazing, Exciting, and Diverse Lives with CYFARS (CYber FARmerS) and Agricultural Virtual Corporation", Presentation at The Asian Federation for Information Technology in Agriculture, Suwon, South Korea.
- Holsapple, C.W., R. Pakath, V.S. Jacob and J.S. Zaveri (1993) "Learning by Problem Processors: Adaptive Decision Support Systems", *Decision Support Systems*, (10)2, pp. 85–108.
- Jacob, V.S. and H. Pirkul (1990) "A Framework for Networked Knowledge-Based Systems", *IEEE Transactions on Systems, Man and Cybernetics*, (20)1, pp. 119–127.
- Jones, M. and G. Taylor (2004) "Data Integration Issues for a Farm Decision Support System", *Transactions in GIS*, (8)4, pp. 459–477.
- Kim, H.-J., K.A. Sudduth and J.W. Hummel (2009) "Soil Macronutrient Sensing for Precision Agriculture", *Journal of Environmental Monitoring*, (11)10, pp. 1810–1824.
- Kitchen, N.R. (2008) "Emerging Technologies for Real-time and Integrated Agriculture Decisions", *Computers and Electronics in Agriculture*, (61)1, pp. 1–3.

- Kitchen, N.R., C.J. Snyder, D.W. Franzen and W.J. Wiebold (2002) "Educational Needs of Precision Agriculture", *Precision Agriculture*, (3)4, pp. 341–351.
- Kloeckl, K., O. Senn and C. Ratti (2012) "Enabling the Real-time City: LIVE Singapore!", *Journal of Urban Technology*, 19(2), pp. 89–112.
- Kohli, R. and V. Grover (2008) "Business Value of IT: An Essay on Expanding Research Directions to Keep Up with the Times", *Journal of the Association for Information Systems*, (9)1, pp. 23–39.
- Kruchkin, A. (2012) "Agribusiness in the US", *Industry Report NN004*, New York, NY: IBISWorld.
- Lamb, D.W., P. Frazier and P. Adams, (2008) "Improving Pathways to Adoption: Putting the Right P's in Precision Agriculture", *Computers and Electronics in Agriculture*, (61)1, pp. 4–9.
- Lederman, R. and L. Wynter (2011) "Real-time Traffic Estimation Using Data Expansion", *Transportation Research, Part B: Methodological*, (45)7, pp. 1062–1079.
- Liu, B. and A. Tuzhilin (2008) "Managing Large Collections of Data Mining Models", *Communications of the ACM*, (51)2, pp. 85–89.
- Livengood, P., R. Maciejewski, C. Wei and D.S. Ebert (2012) "OmicsVis: An Interactive Tool for Visually Analyzing Metabolomics Data", *BMC Bioinformatics*, (13)8, pp. 1–14.
- Maciejewski, R., R. Hafen, S. Rudolph, S.G. Larew, M.A. Mitchell, W.S. Cleveland and D.S. Ebert (2011) "Forecasting Hotspots—A Predictive Analytics Approach", *IEEE Transactions on Visualization and Computer Graphics*, (17)4, pp. 440–453.
- Manheim, M.L. (1989) *Issues in Design of a Symbiotic DSS, Volume 3*, Los Alamitos, CA: IEEE Computer Society Press.
- Marjanovic, O. (2007) "The Next Stage of Operational Business Intelligence: Creating New Challenges for Business Process Management", Presentation at 40th Hawaii International Conference on Systems Science, Waikoloa, Big Island, Hawaii.
- Massey, R.E., D.B. Myers, N.R. Kitchen and K.A. Sudduth (2008) "Profitability Maps as an Input for Site-Specific Management Decision Making", *Agronomy Journal*, (100)1, pp. 52–59.
- McAfee, A. and E. Brynjolfsson (2012) "Big Data: The Management Revolution", *Harvard Business Review*, (90) October 1, pp. 60–68.
- McBee, J. (2012) "Precision Agriculture Systems and Services", *Industry Report OD4422*, New York, NY: IBISWorld.
- McConnell, M. and L.W. Burger (2011) "Precision Conservation: A Geospatial Decision Support Tool for Optimizing Conservation and Profitability in Agricultural Landscapes", *Journal of Soil and Water Conservation*, (66)6, pp. 347–354.
- Mirchandani, D. and R. Pakath (1999) "Four Models for a Decision Support System", *Information and Management*, (35)1, pp. 31–42.
- Mithas, S., N. Ramasubbu and V. Sambamurthy (2011) "How Information Management Capability Influences Firm Performance", *MIS Quarterly*, (35)1, pp. 237–256.
- Muhanna, W.A. and R.A. Pick (1994) "Metamodeling Concepts and Tools for Model Management: A Systems Approach", *Management Science*, (40)9, pp. 1093–1120.
- National Academy of Engineering (2008) "National Academy of Engineering Grand Challenges for Engineering", <http://www.engineeringchallenges.org/cms/challenges.aspx> (current Mar. 22, 2013).
- Niederman, F., R.G. Mathieu, R. Morley and I.-W. Kwon (2007) "Examining RFID Applications in Supply Chain Management", *Communications of the ACM*, (50)7, pp. 92–101.
- Ninomiya, S. (2004) *Successful Information Technology for Agriculture and Rural Development*, Kannondai, Tsukuba, Ibaraki, Japan: National Agricultural Research Center and Organization.
- O'Leary, D. (2008) "Supporting Decisions in Real-time Enterprises: Autonomic Supply Chain Systems", *Information Systems and e-Business Management*, (6)3, pp. 239–255.
- Omid-Najafabadi, M. and S. Bahramnejad (2010) "Determining Research, Education and Extension Requirements for Application of the Precision Agricultural System in Iran", *International Journal of Agricultural Science and Research*, (1)1, pp. 39–48.

- Omidi-Najafabadi, M., S.J.F. Hosseini and S. Bahramnejad (2011) "A Bayesian Confirmatory Factor Analysis of Precision Agricultural Challenges", *African Journal of Agricultural Research*, (6)5, pp. 1219–1225.
- Power, D.J. (2008) "Understanding Data-driven Decision Support Systems", *Information Systems Management*, (25)2, pp. 149–154.
- Prahalad, C.K. (2009) "In Volatile Times, Agility Rules", *Business Week*, September 21, p. 80.
- Ranjan, J. (2008) "Traditional Business Intelligence Vis-a-vis Real-time Business Intelligence", *International Journal of Information and Communication Technology*, (1)3/4, pp. 298–317.
- Rickman, D., J.C. Luvall, J. Shaw, P. Mask, D. Kissel and D. Sullivan (2003) "Precision Agriculture: Changing the Face of Farming", *Geotimes*, November, p. 28.
- Sambamurthy, V., B. Anandhi and V. Grover (2003) "Shaping Agility Through Digital Options: Reconceptualizing the Role of Information Technology in Contemporary Firms", *MIS Quarterly*, (27)2, pp. 237–263.
- Schiefer, G. (2003) "New Technologies and Their Impact on Agriculture, Environment, and the Food Industry", Presentation at European Federation for IT in Agriculture, Food and the Environment, Debrecen, Hungary.
- Sen, T.K, L.J. Moore and T.J. Hess (2000) "An Organizational Decision Support System for Managing the DOE Hazardous Waste Cleanup Program", *Decision Support Systems*, (29)1, pp. 89–109.
- Shoemaker, L., T. Dai and J. Koenig (2005) "TMDL (Total Maximum Daily Load) Model Evaluation and Research Needs", EPA/600/R-05/149, Washington, DC: National Risk Management Research Laboratory, Office of Research and Development, U.S. Environmental Protection Agency.
- Sutherland, J.W. and E.W. Baker (2007) "Relational Model-base Structures, Underpinnings for Decision-driven (vs Database Dependent) Management Support Systems", *Journal of Decision Systems*, (16)1, pp. 101–132.
- Walsh, E., O. Babakina, A. Pennock, H. Shi, Y. Chi, T. Wang and T.E. Graedel (2006) "Quantitative Guidelines for Urban Sustainability", *Technology in Society*, (28)1–2, pp. 45–61.
- Watson, H.J. and B.H. Wixom (2007) "The Current State of Business Intelligence", *Computer*, (40)9, pp. 96–99.

ABOUT THE AUTHORS

Elizabeth White Baker is currently a visiting Assistant Professor in the School of Business at Wake Forest University. Her current research interests include examining the influence of individual beliefs and characteristics on the user of information technology and project management. She also studies strategic decision systems and the technology impact on mergers and acquisitions. Her work appears in *Information Systems Journal*, *Information Technology and People*, the *Journal of Decision Systems*, and *IEEE-Transactions on Engineering Management*.

Copyright © 2013 by the Association for Information Systems. Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and full citation on the first page. Copyright for components of this work owned by others than the Association for Information Systems must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers, or to redistribute to lists requires prior specific permission and/or fee. Request permission to publish from: AIS Administrative Office, P.O. Box 2712 Atlanta, GA, 30301-2712, Attn: Reprints; or via e-mail from ais@aisnet.org.

Communications of the Association for Information Systems

ISSN: 1529-3181

EDITOR-IN-CHIEF

Matti Rossi
Aalto University

AIS PUBLICATIONS COMMITTEE

Virpi Tuunainen Vice President Publications Aalto University	Matti Rossi Editor, CAIS Aalto University	Suprateek Sarker Editor, JAIS University of Virginia
Robert Zmud AIS Region 1 Representative University of Oklahoma	Phillip Ein-Dor AIS Region 2 Representative Tel-Aviv University	Bernard Tan AIS Region 3 Representative National University of Singapore

CAIS ADVISORY BOARD

Gordon Davis University of Minnesota	Ken Kraemer University of California at Irvine	M. Lynne Markus Bentley University	Richard Mason Southern Methodist University
Jay Nunamaker University of Arizona	Henk Sol University of Groningen	Ralph Sprague University of Hawaii	Hugh J. Watson University of Georgia

CAIS SENIOR EDITORS

Steve Alter University of San Francisco	Michel Avital Copenhagen Business School
--	---

CAIS EDITORIAL BOARD

Monica Adya Marquette University	Dinesh Batra Florida International University	Tina Blegind Jensen Copenhagen Business School	Indranil Bose Indian Institute of Management Calcutta
Tilo Böhmann University of Hamburg	Thomas Case Georgia Southern University	Tom Eikebrokk University of Agder	Harvey Enns University of Dayton
Andrew Gemino Simon Fraser University	Matt Germonprez University of Nebraska at Omaha	Mary Granger George Washington University	Douglas Havelka Miami University
Shuk Ying (Susanna) Ho Australian National University	Jonny Holmström Umeå University	Damien Joseph Nanyang Technological University	K.D. Joshi Washington State University
Michel Kalika University of Paris Dauphine	Karlheinz Kautz Copenhagen Business School	Julie Kendall Rutgers University	Nelson King American University of Beirut
Hope Koch Baylor University	Nancy Lankton Marshall University	Claudia Loebbecke University of Cologne	Paul Benjamin Lowry City University of Hong Kong
Don McCubrey University of Denver	Fred Niederman St. Louis University	Shan Ling Pan National University of Singapore	Katia Passerini New Jersey Institute of Technology
Jan Recker Queensland University of Technology	Jackie Rees Purdue University	Jeremy Rose Aarhus University	Saonee Sarker Washington State University
Raj Sharman State University of New York at Buffalo	Thompson Teo National University of Singapore	Heikki Topi Bentley University	Arvind Tripathi University of Auckland Business School
Frank Ulbrich Newcastle Business School	Chelley Vician University of St. Thomas	Padmal Vitharana Syracuse University	Fons Wijnhoven University of Twente
Vance Wilson Worcester Polytechnic Institute	Yajiong Xue East Carolina University		

DEPARTMENTS

Information Systems and Healthcare Editor: Vance Wilson	Information Technology and Systems Editors: Dinesh Batra and Andrew Gemino	Papers in French Editor: Michel Kalika	Debate Karlheinz Kautz
--	---	---	---------------------------

ADMINISTRATIVE

James P. Tinsley AIS Executive Director	Meri Kuikka CAIS Managing Editor Aalto University	Copyediting by S4Carlisle Publishing Services
--	---	--